

A new charged particle detector for KOTO experiment at J-PARC

HongMin KIM, E.J.KIM(Chonbuk National University), G.Y. LIM(KEK)


for the KOTO Collaboration

recenter@naver.com




0. Motivation

- The KOTO Experiment at J-PARC is searching for the $K_L \rightarrow \pi^0 \nu \bar{\nu}$ decay (Branching ratio : 3.0×10^{-11} in Standard Model).



- The number of $K_L \rightarrow \pi^+ \pi^- \pi^0$ events can be reached approximately 2 at SM sensitivity.
- Two new Downstream Charged Veto (DCV) counters (DCV1 and DCV2) were installed in the downstream beam pipe section.
- Due to very limited space, a new scheme of light collection has been implemented.


1. Scheme of DCV



- The fiber goes side by side into the light guide.
- MPPCs are attached to the surface of the scintillator.
- Two pipes (DCV1 and DCV2), total 8 sheets of scintillators.


2. Fabrication Process

1. MPPC Gain Measurement & Fiber Test




- We used the MPPCs from HAMAMATSU S13360-6050PE.
- MPPC were each connected by U.FL Cable (1.32φ)
- Using 430 nm LED, we measured the MPPC single gain.
- MPPCs were grouped into four with the same operating voltage.
- We used the fiber from Kuraray Y-11 (1 mm)
- LED light (430 nm) was injected from one side and the light yield was measured with MPPC from the other side.
- We chose the fiber from the highest value of light yield.


2. Making the scintillator pipe



3. Beam Commissioning



- CC04 and CC05 (surrounding DCV) were used as trigger counter to calibrate with cosmic ray.
- Energy calibration was performed from the calculation of normalized factor for each MPPC to the sum of MPPC's energy.



- Analysis is underway to check the cause of the variation of the calibration factor and the stability of the DCV during the beam time.

4. Summary

- To reduce the $K_L \rightarrow \pi^+ \pi^- \pi^0$ background, it is necessary to install a new scintillator detector (DCV) inside the beam pipe.
- Due to limited space, a new type of light collection is adapted.
- The result of cosmic ray analysis showed DCV got about 60 p.e.
- DCV has been successfully installed at KOTO.
- The calibration of DCV was completed using the cosmic ray.
- Analysis for stability of DCV performance is ongoing.