






Performance check of the charged particle detector for the KOTO experimental at J-PARC.

김홍민, 김은주(전북대), 임계엽(KEK), 안정근, 최재민(고려대)
for the KOTO collaboration

2019 KPS Fall Meeting(2019.10.25.)

The motivation of new detector(DCV)





Background Estimation
(2015 data, S.E.S = 1.3×10^{-9})

source		Number of events
K_L decay	$K_L \rightarrow \pi^+ \pi^- \pi^0$	0.05 ± 0.02
	$K_L \rightarrow 2\pi^0$	0.02 ± 0.02
	other K_L decays	0.03 ± 0.01
	neutron-induced	
hadron-cluster	upstream- π^0	0.24 ± 0.17
	CV- η	0.04 ± 0.03
		0.04 ± 0.02
total		0.42 ± 0.18


• The number of $K_L \rightarrow \pi^+ \pi^- \pi^0$ events can reach approximately 2 at SM sensitivity.

Fabrication of DCV



MPPC : S13360-6050PE from HAMAMATSU

Minimum radius of curvature : 20 mm






- Due to very limited space, we are trying a new scheme of light collection.

- MPPC Gain Measurement(Grouping) > Fiber Light Yield Test(Selection) > Gluing > Evacuation > Wrapping > Cosmic-ray Test > Installation > First Beam Commissioning

- From the Cosmic-ray test, we got 60 p.e. at the center of DCV.

How to do Energy Calibration of DCV

Cosmic-ray tracking




- N_1 : Normalization Factor for each MPPC.
- N_2 : Normalization Factor for a pair of MPPC at Upstream(Downstream)
- N_3 : Normalization Factor for 4 MPPC.


$$\text{Calibration Factor} = \frac{\text{Attenuation Factor}}{N_1 \times N_2 \times N_3 \times \text{PathLengthFactor}} \times M.C. \text{ CorrectionFactor}$$

Data vs M.C.


DCVModuleEnergy distribution for each Cosmic-ray track.



Calibration Factor during Beam Time



● Calibration Factors tend to increase over time



Attenuation Length

- Trigger : DCV Self(Cosmic-ray)
- Hit Condition
 - 1) Hit Module Number = 2
 - 2) ModuleEne > Ene threshold



$$R_E = \frac{E_{up}}{E_{down}} \quad \Delta T = T_{down} - T_{up}$$



$$\ln R_E = \frac{v}{\lambda} \Delta T \quad \begin{array}{l} \lambda = \text{Attenuation Length} \\ v = \text{Propagation Velocity} \end{array}$$

$$y = p_1 x + p_0$$

$$\lambda = \frac{v}{p_1} \quad v = 175 \pm 3 \text{ mm/ns}$$


(From E391a Barrel Photon Detector)

(Y-11(Kuraray) Att. Length > 3500 mm)




Pedestal Stability

Pulse Shape




Pedestal : Mean value of ADC for Sample ID 1 ~ 9

Trend of Pedestal Mean



Pedestal Sigma Distribution. for a physics run.






Asymmetric Gaussian Function

$$f(x) = P_0 \exp\left[-\frac{(x - P_1)^2}{2(P_2 + P_3(x - P_1))^2}\right]$$

P_0 : Normalization factor, P_1 : Mean
 P_2 : Sigma, P_3 : Asymmetric parameter

Pedestal Sigma Stability



Asymmetric Gaussian Function

$$f(x) = P_0 \exp\left[-\frac{(x - P_1)^2}{2(P_2 + P_3(x - P_1))^2}\right]$$

P_0 : Normalization factor, P_1 : Mean
 P_2 : Sigma, P_3 : Asymmetric parameter

- Pedestal Sigma seem to be stable for entire period.

Summary

- To reduce the $K_L \rightarrow \pi^+ \pi^- \pi^0$ background, it is necessary to install a new scintillator detectors(DCV) inside the beam pipe.
- Due to limited space, a new type of light collection is adapted.
- Fabrication and Installation was finished on Feb. 2019
- Energy calibration was done with cosmic rays tagged by surrounding detectors.
- The stability of DCV is being checked.
 - Pedestal Sigma seem to be stable for entire period.
 - Attenuation length is reasonable.